## **T2-C Specifications**

#### Operation

Operation	
Ink Type natura	High Performance water-based dye ink Four 2-liter tanks CMYK
<b>Print Resolution</b>	1600 x 1600 dpi or 1600 x 800 dpi
Print Speed	6 ips (152 mm/sec) or 12 ips (300 mm/sec)
Print Area	Width: 8.8" (223 mm) Length without stitching: 0.6"– 30" (15 mm – 762 mm) Length with stitching: Unlimited
Media Sensors	Adjustable Optical Tracking Edge Sensor supporting Gap, Reflective mark and Continuous media
Connectivity	Ethernet 10/100/1000
Driver	Microsoft® Windows 10, 8, 7, Windows Server® 2012, 2008, 64/32-bit drivers
Software	TrojanControl Software, Microsoft Windows® 10, 8, 7; Windows Server® 2012, 2008, 64/32-bit Drivers
RIP Software	Trojan RIP or Wasatch SoftRIP software option available
Slitting Station	(3) slitter blades included by default, up to (7) slitter blades may be installed and used. Slitting not allowed for continuous material. Cardboard cores with measuring (label width + edge trim) should be ordered.

### Supplies

nk Type	natura	Natura <sup>™</sup> ink, high durability, ex water fastness and good UV lig resistance, food-safe ink.	
9 72 12700000000		18 2900 3200.300000 900000 W	

Label Width	1.9" – 9.8" (50 mm – 250 mm)
Length (Die-cut)	0.6" – 60" (15 mm – 762 mm)
Thickness	4 pt/mil – 12 pt/mil
Roll Size	Core: 3" (76 mm)
	Max. OD: 11.8" (299.7 mm)
Types	Inkiet Coated Tags, Paper, PP, PE.

PET in matte, satin or gloss finish

#### Maintenance

Maintenance Cartridge	Maintenance tray with replaceable modules (wiper roller/print head cap)
Aerosol Extraction System	Replaceable filters

#### Warranty

One-Year Manufacturer's Parts & Labor Warranty (excludes wear parts and supplies)

#### **Environment & Physical**

Operation	Between 68° F – 86° F ( between 20° C –
	30° C) at RH 22 to 80% (non-condensing)
Storage	Between 41° F – 122° F (5° C – 50° C)
	at RH up to 85%, non-condensing at
	149° F (65° C)
Power	100-240V AC 50-60 Hz, 2.5A
Requirements	
Dimensions	With 2 Liter external ink tanks:
	23.8" L x 22.8" W x 31.3" H
	(606 mm x 580 mm x 795 mm)
Touchscreen	7" (177.8 mm) Touchscreen Display
Weight	132.3 lbs. (60 kg) without supplies





The Labels You Want When You Need Them.®

CONTACT US TODAY

www.trojanlabel.com | +1 401-828-4000 | trojanlabel@astronovainc.com



# **T**2-C



The TrojanLabel® T2-C is a one-of-a-kind tabletop label printing press that incorporates the features and functionality of a traditional large production press into a footprint small enough to fit into any size print department. The T2-C is designed for consistent, high-volume 24/7 production. Accurate image placement, tension control, superior print resolution, built-in-slitters, and reduced total cost of ownership, are just some of the key features that make the T2-C so unique.

A perfect combination of ease-of-use, precision, and quality make the **T**2-C an ideal label printing solution designed to give both owners and users peace of mind.

