

# 200T/H Auto Chemistry Analyzer BK-280



## Features:

- ①. 49 Sample positions.
- ②. 56 Reagent positions.
- ③. 120 Reaction cuvettes.
- ④. 200 tests per hour.
- ⑤. Probe with anti-collision function, liquid level detection function.



**Reaction Tray**  
37±0.1°C,  
real-time monitor.



**Mixer Probe**  
Teflon coating to avoid  
cross contamination.



**Reagent Tray**  
2~8°C cooling  
for 24 hours.



**Sample Needle**  
Liquid level sensor function.  
Anti-collision function. Reagent  
volume real-time detection.



**Software**  
User-friendly  
software.



**Washing Probe**  
Independent 4-step  
washing system.

## Parameters:

Model	BK-280	
Overall Performance	Throughput	200 Tests/hour
	Analysis Method	End-point, Fixed-time, Rate(Kinetic), Turbidimetry
	Certificates	CE, FDA, ISO9001, ISO14001, ISO13485
Sample & Reagent System	Sample Positions	49 sample positions
	Reagent Positions	56 reagent positions
	Sample Volume	2~70µl
	Reagent Volume	20~350µl
	Probe	Teflon coating, with anti-collision function, liquid level detection function
	Probe Washing	Automatic washing interior and exterior
	Reagent Cooling	Refrigerated tray with independent switch
Reaction System	Temperature Control	37±0.1°C, real-time monitoring
	Cuvettes	120 reusable cuvettes, optical length 6mm
	Mixer Probe	Independent stirring
	Washing	Automatic cuvettes washing
	STAT function	YES
Optical System	Light Source	12V/30W halogen lamp
	Spectrophotometry	Post-spectral spectrophotometry
	Wavelength	340, 405, 450, 480, 505, 546, 570, 600, 630, 700, 750, 800nm
	Absorbance	0~3.0Abs
Calibration & QC	Calibration	Linear: K factor, 1-point, 2-point and multipoint linear Non-Linear: Spline, Polygon, Index, Ogarithm, Logit-4P, Logit-5P
	Quality Control	Real-time QC, Westgard multi rule, Cumulative sum check, Twin Plot(2D)
Data Management	Software	Windows 7/8/10, 32 or 64 bit
	LIS System	Bi-direction, support HL7 protocol
	Interface	LAN port access
	Printer	External, multiple reporting mode available
Working Conditions	Power Supply	AC220V±10% 50/60Hz, 110V±10% 60Hz, 300W
	Temperature	10~30°C
	Water Consumption	Deionized water: 5L/H
	Humidity	30~80%
Size & Weight	External Size (W*D*H)	950*612*510mm
	Net Weight	75kg
	Package Size (W*D*H)	1118*728*1151mm
	Gross Weight	130kg