

# Galaxy2R® Two-Ram Baler (Wide Model)

| Specifications                                 | 2R310W   | 2R450W  |
|--|--|---|
| <b>Power unit</b>                              | 2x30 / 100 / 2x50 / 2x75                           | 100 / 2x50 / 2x75 / 2x100                         |
| <b>Cycle Time (no load averages)</b>           | 9.8 to 25.2 sec.                                   | 11.1 to 23.9 sec.                                 |
| <b>Compression force</b>                       | 314,160 LBF  | 452,390 LBF                                       |
| <b>Ram face pressure</b>                       | 188 psi  | 270 psi   |
| <b>Feed opening width</b>                      | 57"<br>1448mm                                      | 57"<br>1448mm                                     |
| <b>Feed opening length</b>                     | 70" / 84" / 102"<br>1778mm / 2134mm / 2591mm       | 84" / 102"<br>2134mm / 2591mm                     |
| <b>Baler size (with 70"L feed opening)</b>     | 31'7" x 20'1" x 4'4"<br>9627mm x 6121mm x 1321mm   | N/A   |
| <b>Baler size (with 84"L feed opening)</b>     | 33'10" x 20'1" x 4'4"<br>10312mm x 6121mm x 1321mm | 37'3" x 22'2" x 4'7"<br>11354mm x 6756mm x 1397mm |
| <b>Baler size (with 102"L feed opening)</b>    | 37' x 20'1" x 4'4"<br>11278mm x 6121mm x 1321mm    | 40'3" x 22'2" x 4'7"<br>12268mm x 6756mm x 1397mm |
| <b>Baler weights</b>                           | 77,500 to 91,000 lbs.<br>35153 kg to 41277 kg      | 102,200 to 114,100 lbs.<br>46357 kg to 51755 kg   |
| <b>Bale Weight Data</b>                        |  |   |
| <b>OCC</b>                                     | up to 1,600 lbs.<br>726 kg                         | up to 1,850 lbs.<br>839 kg                        |
| <b>SOP</b>                                     | up to 1,400 lbs.<br>635 kg                         | up to 1,600 lbs.<br>726 kg                        |
| <b>ONP</b>                                     | up to 1,600 lbs.<br>726 kg                         | up to 1,800 lbs.<br>816 kg                        |
| <b>PET</b>                                     | up to 1,300 lbs.<br>590 kg                         | up to 1,600 lbs.<br>726 kg                        |
| <b>HDPE</b>                                    | up to 1,400 lbs.<br>635 kg                         | up to 1,600 lbs.<br>726 kg                        |
| <b>UBC</b>                                     | up to 1,000 lbs.<br>454 kg                         | up to 1,200 lbs.<br>544 kg                        |
| <b>Steel cans</b>                              | up to 2,200 lbs.<br>998 kg                         | up to 2,600 lbs.<br>1179 kg                       |
| <b>MSW</b>                                     | up to 2,200 lbs.<br>998 kg                         | up to 2,500 lbs.<br>1134 kg                       |
| <b>AL extrusions*</b>                          | up to 1,300 lbs.<br>590 kg                         | up to 1,350 lbs.<br>612 kg                        |
| <b>AL siding</b>                               | up to 1,600 lbs.<br>726 kg                         | up to 2,000 lbs.<br>907 kg                        |
| <b>AL/CU radiators</b>                         | up to 1,600 lbs.<br>726 kg                         | up to 2,000 lbs.<br>907 kg                        |
| <b>Misc. AL*</b>                               | up to 2,000 lbs.<br>907 kg                         | up to 2,400 lbs.<br>1089 kg                       |
| * subject to maximum recommended material size |  |   |

## Rental and Leasing Programs Available

## Authorized Dealer:

For detailed specifications, recommendations, or free economic studies comparing various systems, contact Marathon Customer Care at **1-800-633-8974**.



Marathon Equipment Company  
 P.O. Box 1798  
 Vernon, AL 35592-1798  
 800.633.8974  
[www.marathonequipment.com](http://www.marathonequipment.com)  
 NJPA Contract #060612-ESG



www.doveresg.com



Pictures in this literature are illustrative only. Specifications are subject to change without notice in order to accommodate improvements to the equipment. Complies with ANSI standard Z245.5 and applicable OSHA Regulations. Products must be used with safe practice and in accordance with said regulations and standards.